

Isolation Station FLEX

ISFC1000-004

DESCRIPTION:

- Compact & Lightweight
- High Efficiency Low Losses
- Worldwide AC Input Voltages
- Operate on 50/60 Hz
- Medical Isolation Unit
- Low Leakage Current < 100μA

SPECIFICATIONS:

Power: 1000VA

• Input: 100-120V / 200-240V 50/60 Hz

Output: 100-120V
Inlet: IEC 320 C14
Outlet: 6 x NEMA 5-15R

• Input Protec: Fuses

OPTIONS:

Remote Outlet Box
Power-ON Green Light

Input Filter

APPLICATIONS:

- Medical, Dental, and Laboratory Equipment
- IT Management Systems and Network Servers
- Telecommunications and Broadcasting Equipment
- Home and Professional Stereos
- Audio/Video Equipment Systems
- Point of Sales and Data Processing Equipment









Color: White

• Size: 7.2" x 10.2" x 3.48"

• Weight: 10Kgs / 22lbs

• IO Box Depth: 3.00"





- CB Certified to IEC 60601-1:2005 and IEC 60601-1-6:2010
- cTUVus tested to ANSI/AAMI ES60601-1:2005+A2 (R2012)
- CAN/CSA-C22.2 No. 60601-1-6:11 + A1
- IEC 60950(ed.2), IEC 60950-1(ed.2); am1, IEC 60950-1(ed.2)
- CB certified to IEC/EN 60950-1:2005

• RoHS Compliant

CE Marked





www.powertronix.com

1120 Chess Drive, Foster City, CA 94404, USA Tel: (650)345-6800 | sales@powertronix.com

