

Isolation Station™ FLEX

ISFC1000-006

Model: CJ2A2AA-3BB

DESCRIPTION:

- Compact & Lightweight
- High Efficiency - Low Losses
- Worldwide AC Input Voltages
- Operate on 50/60 Hz
- Medical Isolation Unit
- Low Leakage Current < 100µA



SPECIFICATIONS:

- Power: 1000VA
- Input: 100-120V / 200-240V 50/60Hz
- Output: 100-120V / 200-240V
- Inlet: IEC 320 C14
- Outlet: 8 x IEC C13
- Input Protec: 2 x Fuse

- Color: White
- Size: 7.2" x 10.2" x 3.48"
- Weight: 10Kgs / 22lbs
- IO Box Depth: 3.00"

OPTIONS:

- Remote Outlet Box
- Input Filter
- ON/OFF Switch
- Switch-ON Green Light

APPLICATIONS:

- Medical, Dental, and Laboratory Equipment
- IT Management Systems and Network Servers
- Telecommunications and Broadcasting Equipment
- Home and Professional Stereos
- Audio/Video Equipment Systems
- Point of Sales and Data Processing Equipment



SAFETY APPROVALS:

- CB Certified to IEC 60601-1:2005 and IEC 60601-1-6:2010
- cTUVus tested to ANSI/AAMI ES60601-1:2005+A2 (R2012)
- CAN/CSA-C22.2 No. 60601-1-6:11 + A1
- IEC 60950(ed.2), IEC 60950-1(ed.2); am1, IEC 60950-1(ed.2)
- CB certified to IEC/EN 60950-1:2005
- RoHS Compliant

